

## Spectra-Glaze<sup>®</sup> Glazed Block

All units are nominal 8" height and 16" length unless modified as noted below. In some instances only the first two symbols will be used. Other symbols are added as required.

### THE SYMBOLS ARE DERIVED AS FOLLOWS:

- A. The FIRST part is a number denoting the nominal thickness – 1", 2", 4", 6", 8", 10" and 12".
- B. The SECOND part is a letter or combination of letters denoting the general type of unit.
  - S – Stretcher
  - C – Cap Unit
  - G – Cove Base
  - J – Jamb
  - T – Two Face
  - KO – Open Bottom Bond Beam
  - U – Solid Bottom Bond Beam
  - V – Vertically Coursed
  - X – Partially Unglazed Face
  - D – Cove Base Starter
- C. The THIRD part is a letter denoting whether the cap or jamb unit is bullnose or square. In all cases, this letter immediately follows the symbol describing the type of the return unit.
  - P – Square
  - O – Bullnose
- D. The FOURTH part is a number denoting length if units vary from the standard 16" length.
  - Example: 4CP8 is a nominal 4" thick square corner cap, 8" long
- E. The LAST part is a letter denoting the hand of the appropriate return unit.
  - R – Right Hand
  - L – Left Hand
- F. SPECIAL NOTE: For unit heights varying from the nominal 8", the number denoting height immediately follows the number denoting thickness.
  - Example: 44GJO is a nominal 4" thick, 4" high, bullnose corner Base Jamb.
- G. X Units - The X dimension is the portion of the block that is GLAZED. Further the X is a dimension of a 3/4" from the end of the block i.e. 6X8 X2 = a 6x8x8" unit where only 1 3/4" is GLAZED 6XL  
KOBX10 = 6x8x16" 1 Face KO/BB where we are glazing 9 3/4" on Viewers LEFT side